## Script generated by TTT

Title: Petter: Compiler Construction (18.06.2020)

- 35: Local Dependency Graph

Date: Thu Jun 18 09:55:43 CEST 2020


Duration: 06:29 min

Pages: 4

#### Observations

- the local attribute equations need to be evaluated using a global algorithm that knows about the dependencies of the equations
- in order to construct this algorithm, we need
- a sequence in which the nodes of the tree are visited
- a sequence within each node in which the equations are evaluated
- this *evaluation strategy* has to be compatible with the *dependencies* between attributes

We visualize the attribute dependencies D(p) of a production p in a *Local Dependency Graph*:



→ arrows point in the direction of information flow

#### Observations

- the *local* attribute equations need to be evaluated using a *global* algorithm that knows about the dependencies of the equations
- in order to construct this algorithm, we need
- a sequence in which the nodes of the tree are visited
- 2 a sequence within each node in which the equations are evaluated
- this evaluation strategy has to be compatible with the dependencies between attributes

9/69

### Observations

9/69

- in order to infer an evaluation strategy it is not enough to consider the *local* attribute dependencies at each node
- the evaluation strategy must also depend on the *global* dependencies, that is, on the information flow between nodes

10/69

# Observations

- in order to infer an evaluation strategy, it is not enough to consider the *local* attribute dependencies at each node
- the evaluation strategy must also depend on the *global* dependencies, that is, on the information flow between nodes
- ⚠ the global dependencies change with each particular syntax tree
- in the example, the parent node is always depending on children only

   → a depth-first post-order traversal is possible
- in general, variable dependencies can be much *more complex*

10/69

